

CELLULOSE THINNERS

Page: 1

Compilation date: 04/09/2012

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CELLULOSE THINNERS

Product code: CELT

Synonyms: CELLULOSE THINNERS

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London NW2 7TX

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

United Kingdom

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xn: R20/21; Xi: R37; Xn: R40; Xi: R41; Sens.: R43; -: R66

Classification under CLP: Carc. 2: H351; Eye Dam. 1: H318; Flam. Liq. 2: H225; Skin Sens. 1: H317; STOT SE 3:

H335

Most important adverse effects: Highly flammable. Harmful by inhalation and in contact with skin. Irritating to respiratory

system. Limited evidence of a carcinogenic effect. Risk of serious damage to eyes. May cause sensitisation by skin contact. Repeated exposure may cause skin dryness or

cracking.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage. H335: May cause respiratory irritation.

H351: Suspected of causing cancer.

Signal words: Danger

CELLULOSE THINNERS

Page: 2

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark
GHS08: Health hazard







Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical advice/attention.

P310: Immediately call a POISON CENTER or doctor.

Label elements under CHIP:

Hazard symbols: Highly flammable.

Harmful.





Risk phrases: R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R37: Irritating to respiratory system.

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

CELLULOSE THINNERS

Page: 3

Hazardous ingredients:

MIBK

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-550-1	108-10-1	F: R11; Xn: R20; Xi: R36/37; -: R66	Eye Irrit. 2: H319; STOT SE 3: H335; Flam. Liq. 2: H225; Acute Tox. 4: H332; -: EUH066	30-50%
2-BUTANONE	OXIME			
202-496-6	96-29-7	Xn: R21; Xn: R40; Xi: R41; Sens.: R43	Carc. 2: H351; Acute Tox. 4: H312; Eye Dam. 1: H318; Skin Sens. 1: H317	30-50%
ETHANOL				
200-578-6	64-17-5	F: R11 Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	10-30%
BUTAN-1-OL				
200-751-6	71-36-3	-: R10; Xn: R22; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
METHANOL	·			
200-659-6	67-56-1	F: R11; T: R23/24/25; T: R39/23/24/25	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water. Do NOT use solvents or thinners. If irritation persists seek medical attention. Wash

use solvents of triminers. If initiation persists seek medical attention, wash

contaminated clothing before reuse.

Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least

15 minutes, holding the eyelids apart, and seek medical attention.

Ingestion: If accidentally swallowed, wash mouth out with water. Do not induce vomiting, keep at

rest and obtain medical attention. If patient is conscious give plenty of water to drink.

Inhalation: Remove to fresh air, keep the patient warm and at rest. If there is difficulty in breathing,

properly trained personnel may administer oxygen. If breathing has stopped, administer

artificial respiration (NOT mouth to mouth). Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: May cause irritation on prolonged or repeated contact.

Eye contact: Irritation.

Ingestion: Harmful, causing internal irritation. May cause nausea, vomiting, dizziness and

unconsciousness.

Inhalation: Harmful by inhalation. There may be irritation of nose, throat and respiratory tract.

Dizziness, loss of coordination, nausea and vomitting may occur.

CELLULOSE THINNERS

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder. Sand or earth. DO NOT USE WATER.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. May explode in a fire. Solvent vapours may form explosive mixtures with air. The vapour is heavier than air and may travel along the ground, collect in work pits and cellars, creating a fire and respiratory hazard. Vapour may travel considerable distance to source of ignition and flash back. Vapour explosion and poison hazard indoors, outdoors and in sewers. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus. Cool closed containers exposed to fire with water spray. Do NOT allow run-off from fire fighting to enter drains or water courses.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Ventilate the area. Eliminate all sources of ignition. No Smoking. Avoid contact with skin and eyes. Avoid inhaling vapour. The vapour is heavier than air and may collect in confined areas creating a respiratory and explosion hazard. Do not attempt to take action without suitable protective clothing (see section 8). Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. If the product enters drains or sewers, the local water company should be contacted immediately. In the case of contamination of streams, rivers or lakes contact the relevant environment agency. Vapour expolsion and poison hazard indoors, outdoors and in sewers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite. Transfer into a suitable container for disposal in accordance with the waste regulations (see section 13) Do not use equipment in clean-up procedure which may produce sparks. Clean preferably with a detergent, avoid the use of solvents. Clean-up personnel should use respiratory and/or liquid contact protection.

CELLULOSE THINNERS

Page: 5

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid inhalation of vapour. Avoid skin

and eye contact. Smoking, eating and drinking should be prohibited in areas of storage

and use. Emergency shower and eye wash facilities should be readily available.

Exclude sources of heat, sparks and open flame. Earth any equipment used in handling. Use non-sparking tools. The Manual Handling Operations Regulations may apply to the

handling of containers of this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep in cool, dry, ventilated storage and tightly closed containers. Keep away from direct

sunlight. Exclude sources of heat, sparks and open flame. Take precautionary

measures to prevent product spills into drains, the ground or waters.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel

containers. Aluminium is not suitable.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	208mg/m3, 50ppm	416mg/m3, 100ppm	-	

Hazardous ingredients:

ETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	-

BUTAN-1-OL

UK - 154 mg/m3		
----------------	--	--

METHANOL

	/ -	000/ 0		
UK	266 mg/m3		_	_
UIX	200 mg/m3	SSS HIG/HIS	_	-

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

CELLULOSE THINNERS

Page: 6

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by

the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant

occupational exposure limits, suitable respiratory protective equipment should be worn

(see Respiratory protection below).

Respiratory protection: If there is a risk of exposure to high vapour concentrations, use respiratory protective

equipment. All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to

meet the requirements of the COSHH Regulations.

Hand protection: Where repeated skin exposure may occur, wear Nitrile gloves. Wash hands thoroughly

after handling chemicals.

Eye protection: Eye protection designed to protect against liquid splashes should be worn. Ensure eye

bath is to hand.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Clear.
Odour: Pungent

Solubility in water: Partially miscible.

Boiling point/range°C: 82 Flash point°C: 2

Relative density: 0.810 @ 20 C

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and sparks. Moisture. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

CELLULOSE THINNERS

Page: 7

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-BUTANONE OXIME

ORL	MUS	LD50	1	gm/kg
ORL	RAT	LD50	930	mg/kg
SCU	RAT	LD50	2702	mg/kg

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

BUTAN-1-OL

IVN	RAT	LD50	310	mg/kg
ORL	MUS	LD50	2680	mg/kg
ORL	RAT	LD50	790	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation OPT INH		Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: May cause irritation on prolonged or repeated contact.

Eye contact: Irritation.

Ingestion: Harmful, causing internal irritation. May cause nausea, vomiting, dizziness and

unconsciousness.

Inhalation: Harmful by inhalation. There may be irritation of nose, throat and respiratory tract.

Dizziness, loss of coordination, nausea and vomitting may occur.

CELLULOSE THINNERS

Page: 8

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Not expected to bioaccumulate.

12.4. Mobility in soil

Mobility: Volatile. Partially soluble in water. Partially absorbed into soil. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: It is unlikely this material will present an environmental hazard.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

CELLULOSE THINNERS

Page: 9

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: Saftey Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R10: Flammable.

R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R20: Harmful by inhalation.

R21: Harmful in contact with skin.

R22: Harmful if swallowed.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R36/37: Irritating to eyes and respiratory system.

R37/38: Irritating to respiratory system and skin.

R37: Irritating to respiratory system.

R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in

CELLULOSE THINNERS

Page: 10

contact with skin and if swallowed.

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product. As the specific

conditions of use of the product are outside the supplier's control, the user is

responsible for ensuring that the requirements of relevant legislation are complied with.