





Ref: 100 - White Spirit:

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY:

1.1 Product Name: WHITE SPIRIT

Bar codes: 5011338001046 (750ml) – 5011338001060 (2 litre)

1.2 Applications: General purpose cleaner, de-greaser & diluent for oil-based paints.

1.3 Supplier: Palace Chemicals Ltd; Speke Hall Industrial Estate; Speke; Liverpool; L24 4AB

Tel: 0151 486 6101; Fax 0151 448 1982

e-mail: sales@palacechemicals.co.uk; web: www.palacechemicals.co.uk

1.4 Emergency Telephone No. Tel: 0151 486 6101 – Mon-Fri: 0800 - 1800

2. HAZARDS IDENTIFICATION:

2.1 Physical and Chemical Hazards Flam. Liq. 3 - H226

Classification: Human health EUH066;STOT SE 3 - H336;STOT RE 1 - H372;Asp. Tox. 1 - H304

(EC 1272/2008) Environment Aquatic Chronic 2 - H411

2.2

Label elements:

Key Word: DANGER

Hazard statements: H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways. H411 - Toxic to aquatic life with long lasting effects.

H372 - Causes damage to organs Central nervous system through prolonged or repeated exposure if inhaled

H336 - May cause drowsiness or dizziness.

EUH066 - Repeated exposure may cause skin dryness or cracking.

P101 - If medical advice is needed, have product container or label at hand. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautionary P210 - Keep away from heat/sparks/o statements: P102 - Keep out of reach of children.

P103 - Read label before use.

P301 - IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting.

P302/352 - IF ON SKIN: Wash with plenty of soap and water.

P304/340 - IF INHALED: Remove victim to fresh air and keep in a position comfortable for breathing.

P260 - Do not breathe vapours.

P262 - Do not get in eyes, on skin, or on clothing.

2.3 Other hazards: P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P303/361/353 IF ON SKIN Remove immediately all contaminated clothing.

Rinse skin with water/shower.

P403/235 Store in a well-ventilated place. Keep cool.

3. COMPOSITION / INFORMATION ON INGREDIENTS:

3.1 Substance

o.i odbstance						
Name:	CAS No.:	EINECS No.	Concentration:	Classification:		
Naphtha (petroleum) hydro-treated heavy [Type 1]	64742-82-1	919-446-0	100.0%	H226; H304; H411; H066; H366 H372; EUH066		







4. FIRST AID MEASURES:

4.1 Description of measures:

EYE CONTACT: Irrigate thoroughly for 15 minutes with clean running water or a boric saline eye wash bottle.

Seek medical attention should eye irritation persist or become inflamed.

INHALATION: Avoid working in a poorly ventilated, confined space. Remove to fresh air and rest. If irritation or

breathing difficulties persist, seek medical attention.

SKIN CONTACT: Wash off skin with warm soapy water. Remove contaminated clothing and launder regularly.

Prolonged and unattended contact should be avoided. Where irritation to skin is apparent seek

medical attention.

INGESTION: Clean out mouth with copious volumes of water and drink plenty. Do not induce vomiting.

Beware of aspiration if vomiting occurs. Seek prompt medical attention and show this data sheet

4.2 Acute & Chronic symptoms:

Inhalation: Vapours inhaled in strong concentration have a narcotic effect on the central nervous system.

Irritation of the respiratory tract due to excessive fumes causes headache, drowsiness or other

effects to the central nervous system, loss of consciousness.

Ingestion: Nausea, vomiting, abdominal pain.

Skin contact: Prolonged or repeated contact may cause irritation and dry skin.

Eye Contact: Burning feeling and temporary redness.

4.3 Immediate medical attention: This will be needed to resolve the most severe risk which is through ingestion as the product

may enter the lungs due to its low viscosity and lead to the rapid development of very serious

inhalation pulmonary lesions (medical survey during 48 hours).

5. FIRE FIGHTING MEASURES:

5.1 Extinguishing media: Dry powder; Foam, C02 – Do not use water jets.

5.2 Combustion Hazards: Hazardous decomposition when subject to combustion – will produce noxious, irritating fumes.
 5.3 Advice for fire-fighters: Use approved self-contained breathing apparatus. Only use a fine water spray to cool down

5.3 Advice for fire-fighters: Use approved self-contained breathing apparatus. Only use a fine water spray to cool down heat affected containers – not burning product. Cool containers exposed to flames with water

until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water

control.

6. ACCIDENTAL RELEASE MEASURES:

6.1 Personal protection: Ventilate area and eliminate all sources of ignition. Wear personal protective equipment

recommended in section 8.

6.2 Environmental precautions: Do not allow spill to enter drains or watercourses. Form a dam with sand, earth or a boom.

Absorb, bund and scrape spillages onto sand, sawdust or absorbent granules.

6.3 Spill removal methods: Confine residues in clearly marked sealed containers for disposal in accordance with Local

Authority regulations for flammable products – subject to special waste management controls.

6.4 References to other sections: Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for

additional information on health hazards. For waste disposal, see section 13.

7. HANDLING & STORAGE:

7.1 Safe handling precautions: Eliminate all sources of ignition. Risk of vapour concentration on the floor and in low-lying areas.

Static electricity and formation of sparks must be prevented. Use explosion proof electric equipment. Wear full protective clothing for prolonged exposure and/or high concentrations. Contaminated clothing and shoes must be discarded. Contaminated rags and cloths must be put in fireproof containers for disposal. Ventilate well, avoid breathing vapours. Use approved

respirator if air contamination is above accepted level.

7.2 (a) Safe storage conditions: Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original

container. Take precautionary measures against static discharges.

7.2 (b) Incompatible materials: Keep away from oxidisers, heat and flames. May attack some plastics, rubber and coatings.

7.3 Specific end uses: The identified uses for this product are detailed in Section 1.2.



MATERIAL SAFETY DATA SHEET VERSION 2 - CLP-GHS CLASSIFICATIONS (EC) NO. 1272/2008



8. EXPOSURE CONTROLS & PERSONAL PROTECTION:

8.1 Control parameters

Substance: 8 hour exposure limit 15 minute exposure limit Source. Type

White Spirit WEL- 350 mg/M3 STEL- 600mg/M3

DNEL's - (Derived No effect levels) for workers:

Exposure pattern:	Route	DNEL		Dose descriptor	
Acute systemic effects -	Dermal				
Acute systemic effects -	Inhalation	330 per 8 hours mg/m3	3	Industry	
Acute Local effects -	Dermal				
Acute Local effects -	Inhalation	71 per 24 hours mg/m3	3	Consumer	
Long term systemic effects -	Dermal	44 mg/kg/day		Industry	
Long term systemic effects -	Inhalation				
Long term local effects -	Dermal	26 mg/kg/day		Consumer	
Long term local effects -	Inhalation				
PNEC's - Predicted No effect concentration (Environment):					
Compartment:	PNEC Dose D		Dose De	scriptor	
Fresh water -					
Sewage treatment -					

8.2 Exposure controls:

Engineering controls: Provide adequate general and local exhaust ventilation.

Respiratory protections: No specific recommendation is made, but appropriately specified respiratory protection must be

used if the general level exceeds the recommended occupational exposure limit.

Hand protection: Protective gloves must be used. The most suitable glove must be chosen in

consultation with the gloves supplier, who can inform about the breakthrough

time of the glove material. Use protective gloves made of nitrile.

Eye protection: BS 2092 approved safety Goggles should be worn for all applications to help

prevent accidental face/eye contact.

Other Protection: Wear appropriate clothing to prevent any possibility of liquid contact and

repeated or prolonged vapour contact.

Hygiene measures: DO NOT SMOKE IN WORK AREA!

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9. PHYSICAL & CHEMICAL PROPERTIES:

Appearance: Water white **Relative density:** 0.775 – 0.795

Odour:Aromatic hydrocarbonWater solubility:NilOdour threshold:LowerSolubility in oils:100%pH:n/aPartition coefficient (Kow):n/aFlash point:40°CAuto-ignition temperature:>230

Melting point: 40 C Decomposition temperature: 7200

Melting point: 40 C Decomposition temperature: 7200

Boiling point: 150 – 200'C Surface tension: 0.0245

Boiling point: 150 – 200°C **Surface tension:** 0.0245 N/m @ 25 °C **Evaporation rate:** 65 (Et Et=1) – DIN 53170 **Viscosity:** 0.95 m2/s 40

Upper/Lower Flam limits: 7.0% - 0.6% Explosive properties: May form explosive mixtures with air.

Vapour pressure:< 5 kPa 20</th>Oxidising properties:n/aVapour density:n/aParticle size:n/a

10. STABILITY & REACTIVITY:

10.1 Conditions to avoid: Sources of ignition. Avoid 10.4 Reactivity: Stable except when ignited

static discharge.

10.2 Incompatible Materials: Acids & Oxidising agents **10.5 Chemical reactivity:** Stable under the prescribed

storage conditions.

10.3 Decomposition hazards: Fire creates toxic fumes **10.6 Risk of hazardous reaction:** None under normal use.







11. TOXICOLOGICAL INFORMATION:

11.1 Information on toxicological effects: This product has not been exhaustively tested. Judgements on the expected toxicity of this product have been made based upon consideration of its' major components.

Routes of exposure: Inhalation, skin contact and

ingestion.

Eye damage/irritation: Burning feeling and temporary

redness.

Reproductive toxicity: n/a

STOT single exposure:

Toxic dose 1 - LD 50 >5050

mg/kg (oral rat)

STOT repeat exposure: Target Organs - Central

nervous system Respiratory

system, lungs

Skin Corrosivity / Irritation: May cause de-fatting of the

skin, n/a

Respiratory/skin sensitisation:

Germ cell Mutagenicity: n/a

Carcinogenicity: No evidence of carcinogenic

properties

Aspiration hazard: The fluid can enter the lungs

and cause damage (chemical pneumonitis, potentially fatal).

12. ECOLOGICAL INFORMATION:

12.1 Ecotoxicity: Acute Toxicity - Fish

LC50 96 hours ~ 30 mg/l

12.2 Bio-accumulative potential: Negligible due to high

volatility

12.3 Persistence & degradability: The substance is readily

biodegradable.

12.4 Mobility in soil: 75% degradable in 28 days

12.5 PBT and vPvB result: Not Classified as PBT/vPvB

12.6 Other adverse effects: n/a

13. DISPOSAL CONSIDERATIONS:

13.1 Waste treatment Methods: Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

Waste is suitable for incineration. Rags and the like, moistened with flammable liquids, must be discarded into designated fireproof bucket. Where possible packaging should be collected for

reuse or recycling.

When this product, in its liquid state, as supplied becomes waste it should be disposed of as hazardous waste using the waste code 08 01 11 waste paint and varnish containing organic solvents or other dangerous substances. Empty used containers should be disposed of as waste code 15 01 10 packaging containing residues of or contaminated by dangerous substances. When used the removed sludge should be disposed of using waste code 08 01 13 for paint & varnish sludge materials. Any absorbents used for clearing up soils should be disposed of using waste code 15 02 02, for absorbents contaminated by dangerous substances.

14. TRANSPORT INFORMATION:

Transport Labels:





Regulatory Code (Land, Sea & Air):	ADR	IMDG	ICAO	
14.1 UN No.:	1300	1300	1300	
14.2 Proper shipping name:	Turpentine Substitute	Turpentine Substitute	Turpentine Substitute	
14.3 ADR Packing Group:	III	III	III	
14.4 Transport Hazard Class:	3	3	3	
14.5 Environmental hazards.	Marine pollutant	Marine pollutant	Marine pollutant	
14.6 Special user precautions:	Emergency Action Code 3Y	EMS F-E, S-E	HAZCHEM CODE 3YE	
14.7 Transport in bulk – IBC code:	HAZARD No. (ADR) 33	Tunnel Restriction Code (D/E)	







15. REGULATORY INFORMATION:

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture

All components are listed as existing substances in Europe

UK Regulatory References:

Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

Environmental Listing - Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980.

Statutory Instruments:

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes:

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

EU Legislation:

Dangerous Substance Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission

Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National Regulations:

Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product. The guidelines given in the HSE publication COSHH ESSENTIALS - Easy Steps To Control Chemicals gives sound advice for deciding safe working control measures.

Authorisations (Title VII Regulation 1907/2006) - No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006) - No specific restrictions of use are noted for this product.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this product.

16. OTHER INFORMATION:

Last revision date: 11th December 2014

SDS No.: 100

List of abbreviations used in this SDS:

CAS Chemical abstracts service

CLP Classification, labelling & packaging regulation (EC) No. 1272/2008

DSD Dangerous substances Directive 67/548/EEC
DPD Dangerous Products Directive 1999/45/EC
PBT Persistent, Bio-accumulative & Toxic

REACH Registration, Evaluation, Authorisation & Restriction of Chemicals Regulation (EC) 1907/2006

vPvB Very Persistent, very Bio-accumulative

References: Volume VII Approved supply list; EH40; Croner; Bulk supplier data sheets

Classification methods:

H Phrases in section 3 H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways. H411 - Toxic to aquatic life with long lasting effects.

H066 - Repeated exposure may cause skin dryness or cracking.

H336 - May cause drowsiness or dizziness.

H372 - Causes damage to organs Central nervous system through prolonged or repeated

exposure if inhaled

EUH066 - Repeated exposure may cause skin dryness or cracking.

Training for workers:

Disclaimer: The information supplied in this safety data sheet is intended to assist in the use of the above product without risk to safety and health and is based on current knowledge and experience of the associated physico-chemical hazards. The data does

not signify any warranty with regard to the product's properties. This information may be used to assist in formulating a

 ${\it COSHH risk assessment if applied at work. This data sheet complies with EC Directive 91/155EC.}$