



# SAFETY DATA SHEET

Page 1 of 4

## Supreme Wax

Revision 0  
Revision date 11-May-2010

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

**Product name** Supreme Wax  
**Company** Fiddes & Son Ltd  
Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX  
info@fiddes.co.uk  
www.fiddes.co.uk  
**Telephone** +44 (0)29 2034 0323  
**Fax** +44 (0)29 2034 3235

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

#### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Naphtha (petroleum), hydrotreated light	40 - 50%	64742 49-0		N;R51/53 Xn;R65
n-Hexane	10 - 20%	110-54-3	203-777-6	F; R11 Repr Cat 3; R62 Xn; R65-48/20 Xi; R38 R67 N; R51/53
Cyclohexane	1 - 10%	110-82-7	203-806-2	F; R11 Xn; R65 Xi; R38 R67 N; R50/53
Methylcyclohexane	10 - 20%	108-87-2	203-624-3	F; R11 Xn; R65 Xi; R38 R67 N; R51/53

### 3. HAZARDS IDENTIFICATION

**Main hazards** Highly flammable. Irritating to skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of impaired fertility. Harmful: may cause lung damage if swallowed.

### 4. FIRST AID MEASURES

**Skin contact** Wash off immediately with plenty of soap and water. Remove contaminated clothing.  
**Eye contact** Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.  
**Inhalation** Move the exposed person to fresh air. Seek medical attention.  
**Ingestion** DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention.  
**General information** If you feel unwell, seek medical advice (show the label where possible). Keep the affected person warm and at rest. Remove contaminated clothing. Wash all contaminated clothing before reuse.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media** Use extinguishing media appropriate to the surrounding fire conditions.  
**Fire hazards** Burning produces irritating, toxic and obnoxious fumes.  
**Protective equipment** Wear: Self-contained breathing apparatus.

Print date 14-May-2010

# Supreme Wax

Revision 0  
Revision date 11-May-2010

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Avoid raising dust. Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area.
<b>Environmental precautions</b>	Do not allow product to enter drains.
<b>Clean up methods</b>	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Appropriate local exhaust ventilation is required. Wear suitable protective equipment.
<b>Storage</b>	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits

n-Hexane	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 72 WEL 15 min limit mg/m3: -
Cyclohexane	WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 300	WEL 8-hr limit mg/m3: 350 WEL 15 min limit mg/m3: 1050

<b>Engineering measures</b>	Ensure adequate ventilation of the working area.
<b>Respiratory protection</b>	Wear: Suitable respiratory equipment. Suitable half mask respirator with filter P3 (EN 143)
<b>Hand protection</b>	Chemical resistant gloves (PVC)
<b>Eye protection</b>	Approved safety goggles.
<b>Protective equipment</b>	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Description</b>	Solid.
<b>Odour</b>	Characteristic.
<b>Flash point</b>	16°C
<b>Water solubility</b>	insoluble in water.

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Stable under normal conditions.
<b>Conditions to avoid</b>	Heat, sparks and open flames.
<b>Materials to avoid</b>	Combustible materials. Oxidising agents.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

<b>Acute toxicity</b>	Harmful if swallowed.
<b>Corrosivity</b>	May cause irritation to skin.
<b>Repeated or prolonged exposure</b>	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	No data is available on this product.
--------------------	---------------------------------------

# Supreme Wax

Revision 0  
Revision date 11-May-2010

## 13. DISPOSAL CONSIDERATIONS

**General information** Can be incinerated if in compliance with local and national regulations. Dispose of in compliance with all local and national regulations.

## 14. TRANSPORT INFORMATION

### ADR/RID

UN 1263	Packing group II
Class 3	Hazard ID 33
Proper Shipping Name PAINT .	

### IMDG

UN 1263	Packing group II
Class 3	Marine pollutant .
EmS Code F-E S-E	

### IATA

UN 1263	Packing group II
Class 3	Subsidiary risk -
Packing Instruction 307 (Cargo)	Maximum quantity 60 L
Packing Instruction 305 (Passenger)	Maximum quantity 5 L

## 15. REGULATORY INFORMATION

**Labelling** The product is classified in accordance with 67/548/EEC.

**Symbols** F - Highly flammable; Xn - Harmful; N - Dangerous for the environment



### Risk phrases

R11 - Highly flammable.  
R38 - Irritating to skin.  
R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R62 - Possible risk of impaired fertility.  
R65 - Harmful: may cause lung damage if swallowed.

### Safety phrases

S1/2 - Keep locked up and out of the reach of children.  
S13 - Keep away from food, drink and animal feedingstuffs.  
S23 - Do not breathe gas/fumes/vapour/spray.  
S25 - Avoid contact with eyes.  
S16 - Keep away from sources of ignition - No smoking.  
S29 - Do not empty into drains.  
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

# Supreme Wax

Revision 0  
Revision date 11-May-2010

## 16. OTHER INFORMATION

<b>Text of risk phrases in Section 2</b>	<p>R11 - Highly flammable. R38 - Irritating to skin. R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R62 - Possible risk of impaired fertility. R65 - Harmful: may cause lung damage if swallowed. R67 - Vapours may cause drowsiness and dizziness.</p>
<b>Revision</b>	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>