

**SAFETY DATA SHEET**  
**9005/519 HCF WHITE PRECATALYST PRIMER**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

**Product Name** 9005/519 HCF WHITE PRECATALYST PRIMER

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Industrial wood coating.

**1.3. Details of the supplier of the safety data sheet**

**Supplier:** Morrells Woodfinishes Ltd  
Wellington Works  
Mill Lane, Woodley  
Stockport  
England  
SK6 1RN  
0161 406 5300  
0161 406 6276  
enquiries@morrells.co.uk

**1.4. Emergency telephone number**

0161 406 5300 DURING OFFICE HOURS

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**

Physical	Flam. Liq. 2 - H225
Health	EUH066; Eye Irrit. 2 - H319; STOT Single 3 - H336
Environmental	Not classified.

**Classification (1999/45)** Xi; R36. F; R11. R66, R67.

**Human Health**

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

**Environment**

The product is not expected to be hazardous to the environment.

**Physical And Chemical Hazards**

The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures.

**2.2. Label elements**

**Label In Accordance With (Ec) No. 1272/2008**



**Signal Word** Danger

**Hazard Statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

## 9005/519 HCF WHITE PRECATALYST PRIMER

### Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/attention.
P370+378	In case of fire: Use ... for extinction.

### Supplementary Precautionary Statements

P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337	If eye irritation persists:
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

### Supplemental Label Information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

<b>ACETONE</b>	<b>5-10%</b>
<b>CAS-No.: 67-64-1</b>	<b>EC No.: 200-662-2</b>
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R36 R66 R67
<b>ETHANOL</b>	<b>10-30%</b>
<b>CAS-No.: 64-17-5</b>	<b>EC No.: 200-578-6</b>
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548) F;R11
<b>ISOBUTYL ACETATE</b>	<b>10-30%</b>
<b>CAS-No.: 110-19-0</b>	<b>EC No.: 203-745-1</b>
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066	Classification (67/548) F;R11 R66

**9005/519 HCF WHITE PRECATALYST PRIMER**

<b>METHANOL</b>		<b>&lt; 1%</b>
<b>CAS-No.: 67-56-1</b>	<b>EC No.: 200-659-6</b>	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT Single 1 - H370	Classification (67/548) F;R11 T;R23/24/25,R39/23/24/25	
<b>PROPAN-1-OL</b>		<b>5-10%</b>
<b>CAS-No.: 71-23-8</b>	<b>EC No.: 200-746-9</b>	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R41 R67	
<b>XYLENE</b>		<b>5-10%</b>
<b>CAS-No.: 1330-20-7</b>	<b>EC No.: 215-535-7</b>	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548) R10 Xn;R20/21 Xi;R38	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

**Composition Comments**

The data shown are in accordance with the latest EC Directives.

**SECTION 4: FIRST AID MEASURES**

**4.1. Description of first aid measures**

**General Information**

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

**Inhalation.**

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

**Ingestion**

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

**Skin Contact**

Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

**Eye Contact**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

**4.2. Most important symptoms and effects, both acute and delayed**

**4.3. Indication of any immediate medical attention and special treatment needed**

**SECTION 5: FIREFIGHTING MEASURES**

**5.1. Extinguishing media**

**Extinguishing Media**

Use: Alcohol resistant foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc. DO NOT use water if avoidable.

# 9005/519 HCF WHITE PRECATALYST PRIMER

## 5.2. Special hazards arising from the substance or mixture

### Unusual Fire & Explosion Hazards

Fire causes formation of toxic gases.

### Specific Hazards

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

## 5.3. Advice for firefighters

### Special Fire Fighting Procedures

Keep run-off water out of sewers and water sources. Dike for water control.

### Protective Measures In Fire

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

Do not discharge onto the ground or into water courses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

### 6.3. Methods and material for containment and cleaning up

Keep combustibles away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Wash contaminated area with water. Wash thoroughly after dealing with a spillage.

### 6.4. Reference to other sections

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Do not use contact lenses. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Use explosion proof electric equipment. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### Storage Class

Flammable liquid storage.

### 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	500 ppm	1210 mg/m <sup>3</sup>	1500 ppm	3620 mg/m <sup>3</sup>	
ETHANOL	WEL	1000 ppm	1920 mg/m <sup>3</sup>			
ISOBUTYL ACETATE	WEL	150 ppm	724 mg/m <sup>3</sup>	187 ppm	903 mg/m <sup>3</sup>	
METHANOL	WEL	200 ppm	266 mg/m <sup>3</sup>	250 ppm	333 mg/m <sup>3</sup>	
PROPAN-1-OL	WEL	200 ppm(Sk)	500 mg/m <sup>3</sup> (Sk)	250 ppm(Sk)	625 mg/m <sup>3</sup> (Sk)	
XYLENE	WEL	50 ppm(Sk)	220 mg/m <sup>3</sup> (Sk)	100 ppm(Sk)	441 mg/m <sup>3</sup> (Sk)	

WEL = Workplace Exposure Limit.

### Ingredient Comments

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

### 8.2. Exposure controls

#### Protective Equipment

# 9005/519 HCF WHITE PRECATALYST PRIMER



## Process Conditions

Provide eyewash station.

## Engineering Measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

## Hand Protection

Protective gloves and goggles must be used if there is a risk of direct contact or splash.

## Eye Protection

Contact lenses should not be worn when working with this chemical! Wear approved safety goggles.

## Other Protection

Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.

## Hygiene Measures

Wash promptly if skin becomes contaminated. Promptly remove non-impervious clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	White / off-white
Initial Boiling Point and Boiling Range:	90
Flash Point (°C)	8

### 9.2. Other information

Volatile Organic Compound (VOC)	587 g/litre
---------------------------------	-------------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

No particular stability concerns.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. Vapours have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

#### Ingestion.

Gastrointestinal symptoms, including upset stomach.

#### Skin Contact

Repeated exposure may cause skin dryness or cracking.

#### Eye Contact

Irritating and may cause redness and pain.

## SECTION 12: ECOLOGICAL INFORMATION

# 9005/519 HCF WHITE PRECATALYST PRIMER

## Ecotoxicity:

The product is not expected to be hazardous to the environment.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

### General Information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

### 13.1. Waste treatment methods

Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point. Make sure containers are empty before discarding (explosion risk).

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

UN No. (ADR/RID/ADN) 1263

### 14.2 UN Proper Shipping Name

PAINT OR PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

### Transport Labels



### 14.4. Packing group

ADR/RID/ADN Packing group II

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

### 14.6. Special precautions for user

EMS F-E, S-D

Emergency Action Code 3YE

Hazard No. (ADR) 33

Tunnel Restriction Code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Uk Regulatory References

Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

# 9005/519 HCF WHITE PRECATALYST PRIMER

## Statutory Instruments

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

## Approved Code Of Practice

Safety Data Sheets for Substances and Preparations.

## Guidance Notes

Spraying of Highly Flammable Liquids EH9. Introduction to Local Exhaust Ventilation HS(G)37.

## National Regulations

Workplace Exposure Limits 2005 (EH40)

## 15.2. Chemical Safety Assessment

### SECTION 16: OTHER INFORMATION

**Revision Date** 15/09/2015

**Revision** 2

**Supersedes Date** 01/02/2012

#### Risk Phrases In Full

R10 Flammable.

R11 Highly flammable.

R20/21 Harmful by inhalation and in contact with skin.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R38 Irritating to skin.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

R41 Risk of serious damage to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

#### Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs <<Organs>>.